

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** WIL-GRO DESERT IRON 20-0-10  
**Other means of identification** None.  
**Recommended use** Ag Product - Plant Nutrition  
**Recommended restrictions** Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

### Manufacturer/Importer/Supplier/Distributor information

#### Manufacturer

**Company name** Wilbur-Ellis Company LLC  
**Address** Wilbur-Ellis Company LLC  
16300 Christensen Rd. Ste 135  
Tukwila, WA 98188  
United States  
**Telephone** Branded Products Information (800) 500-1698  
**E-mail** SDS@wilburellis.com  
**Emergency phone number** Chemtrec - Domestic (800) 424-9300  
Chemtrec - International +1 703-741-5970

## 2. Hazard(s) identification

**Physical hazards** Not classified.  
**Health hazards** Carcinogenicity Category 1A  
**Environmental hazards** Not classified.  
**OSHA defined hazards** Not classified.

#### Label elements



**Signal word** Danger  
**Hazard statement** May cause cancer.  
**Precautionary statement**  
**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, and face protection.  
**Response** IF exposed or concerned: Get medical attention.  
**Storage** Store locked up.  
**Disposal** Dispose of contents and container in accordance with government regulations.  
**Hazard(s) not otherwise classified (HNOC)** None known.  
**Supplemental information** None.

## 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ammonium Sulfate		7783-20-2	50 - < 60
Muriate of Potash		7447-40-7	10 - < 20
Urea		57-13-6	10 - < 20

Chemical name	Common name and synonyms	CAS number	%
Crystalline Silica (Quartz)		14808-60-7	< 0.2
Other components below reportable levels			5 - < 10

Percentage ranges of composition to protect confidentiality or due to batch variation.

#### 4. First-aid measures

<b>Inhalation</b>	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Rinse skin with water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Use water spray to cool unopened containers.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide appropriate exhaust ventilation at places where dust is formed. Keep formation of airborne dusts to a minimum. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities</b>	Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

##### Occupational exposure limits

##### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Crystalline Silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Crystalline Silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Crystalline Silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

**US. Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value	Form
Urea (CAS 57-13-6)	TWA	10 mg/m3	Total particulate.

<b>Biological limit values</b>	No biological exposure limits noted for the ingredient(s).
<b>Exposure guidelines</b>	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.
<b>Appropriate engineering controls</b>	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Not normally needed.
<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves.
<b>Other</b>	Wear suitable protective clothing. Use of an impervious apron is recommended.
<b>Respiratory protection</b>	Use a particulate filter respirator for particulate concentrations exceeding the Occupational Exposure Limit.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance**

<b>Physical state</b>	Solid.
<b>Form</b>	Solid.
<b>Color</b>	Not available.
<b>Odor</b>	Not available.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	270.86 °F (132.7 °C) estimated
<b>Initial boiling point and boiling range</b>	2732 °F (1500 °C) estimated
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.

<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	0.00001 hPa estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	1.71 g/cm3 estimated
<b>Specific gravity</b>	1.71 estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Dust in the eyes will cause irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Irritation of eyes. Upper respiratory tract irritation.

### Information on toxicological effects

<b>Acute toxicity</b>	Harmful if inhaled.
-----------------------	---------------------

Components	Species	Test Results
Ammonium Sulfate (CAS 7783-20-2)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Mouse	> 2000 mg/kg
	Rat	> 2000 mg/kg
<b>Oral</b>		
LD50	Rat	4250 mg/kg
Muriate of Potash (CAS 7447-40-7)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	3020 mg/kg

Components	Species	Test Results
Urea (CAS 57-13-6)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Mouse	13000 mg/kg
	Rat	15000 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.
<b>Serious eye damage/eye irritation</b>	Dust in the eyes will cause irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not available.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. Risk of cancer cannot be excluded with prolonged exposure.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline Silica (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

#### US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline Silica (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not available.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. May cause damage to organs through prolonged or repeated exposure.

## 12. Ecological information

<b>Ecotoxicity</b>	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
<b>Persistence and degradability</b>	No data is available on the degradability of this product.
<b>Bioaccumulative potential</b>	No data available.
<b>Mobility in soil</b>	No data available.
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents and container in accordance with government regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings, if applicable, even after container is emptied.

### 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

### 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are listed on or exempted from the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - No  
Delayed Hazard - Yes  
Fire Hazard - No  
Pressure Hazard - No  
Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** No

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
AMMONIA (INCLUDES ANHYDROUS AMMONIA AND AQUEOUS AMMONIA FROM WATER DISSOCIABLE AMMONIUM SALTS AND OTHER SOURCES; 10% OF TOTAL AQUEOUS AMMONIA IS REPORTABLE UNDER THIS LISTING)	783-20-2	50 - < 60

#### Other federal regulations

##### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

##### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**US state regulations**

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Crystalline Silica (Quartz) (CAS 14808-60-7)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Crystalline Silica (Quartz) (CAS 14808-60-7) Listed: October 1, 1988

**16. Other information, including date of preparation or last revision**

**Issue date** 05-22-2015  
**Revision date** 03-29-2017  
**Version #** 03  
**NFPA ratings** Health: 1  
Flammability: 0  
Instability: 0

**NFPA ratings**



**Disclaimer**

This information was developed from information on the constituent materials. No warranty is expressed or implied regarding the completeness or continuing accuracy of the information contained herein, and Wilbur-Ellis disclaims all liability for reliance thereon. The user should satisfy himself that he has all current data relevant to his particular use.