

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Mixture Product name : Tank Cleaner Product code 20097

1.2. Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet

Farmers Business Network 1123 Industrial Road Suite 200 San Carlos, CA 94070 T 1-844-200-3276

annie@farmersbusinessnetwork.com - www.farmersbusinessnetwork.com

Emergency telephone number

Emergency number : 1-800-424-9300 ChemTrec

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS-US classification

Skin Corr. 1A H314

Full text of H-statements: see section 16

Label elements 2.2.

GHS-US labelling

Hazard pictograms (GHS-US)



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H314 - Causes severe skin burns and eye damage Precautionary statements (GHS-US) P260 - Do not breathe fumes, mists, spray or vapors

P264 - Wash hands, forearms and face thoroughly after handling

P280 - Wear Eye protection, Face protection, Skin protection. Clothing protection

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call Call a POISON CENTER or doctor/physician

P321 - Specific treatment (see additional precautions on this label)

P363 - Wash contaminated clothing before reuse

P405 - Store locked up

P501 - Dispose of contents/container to a licensed hazardous waste facility in accordance with

state and local agencies

Other hazards

No additional information available

Unknown acute toxicity (GHS-US)

Not applicable

01/17/2017 EN (English) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

Substance

Not applicable

32 **Mixture**

Name	Product identifier	%	GHS-US classification
potassium hydroxide	(CAS No) 1310-58-3	5 - 25	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Aquatic Acute 3, H402
disodium metasilicate	(CAS No) 6834-92-0	1 - 10	Skin Corr. 1A, H314
2-aminoethanol	(CAS No) 141-43-5	1 - 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314

Full text of H-statements: see section 16

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately First-aid measures after inhalation

call a POISON CENTER or doctor/physician.

First-aid measures after skin contact Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a POISON CENTER or doctor/physician.

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to First-aid measures after eve contact

do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or

doctor/physician.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage

Indication of any immediate medical attention and special treatment needed

No additional information available

First-aid measures after ingestion

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Reactivity : Thermal decomposition generates : Corrosive vapours.

Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures 6.1.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Ventilate area. **Emergency procedures**

Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

01/17/2017 EN (English) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : May be corrosive to metals.

Precautions for safe handling : Avoid contact with skin, eyes and clothing.

Hygiene measures : Wash ... thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage temperature : $>= 25 (5 - 42) ^{\circ}C$

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tank Cleaner	
ACGIH	Not applicable
OSHA	Not applicable
disodium metasilicate (6834-92-0)	
400111	No. 4 man Para Dala

disodium metasiicate (6634-32-0)	
ACGIH	Not applicable
OSHA	Not applicable

potassium hydroxide (1310-58-3)		
ACGIH	ACGIH Ceiling (mg/m³)	2 mg/m³ (Potassium hydroxide; USA; Momentary value; TLV - Adopted Value)
OSHA	Not applicable	

2-aminoethanol (141-43-5)		
ACGIH	ACGIH TWA (ppm)	3 ppm (Ethanolamine; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	6 ppm (Ethanolamine; USA; Short time value; TLV - Adopted Value)
OSHA	Not applicable	

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or face shield.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : red

Odour : Characteristic odour Odour threshold : No data available

pH : >= 13

Melting point : No data available

01/17/2017 EN (English) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing point : $<= 0 \, ^{\circ}\text{C}$ Boiling point : $>= 100 \, ^{\circ}\text{C}$ Flash point : None

Relative evaporation rate (butylacetate=1) : No data available Flammability (solid, gas) : No data available Explosive limits : No data available : No data available Explosive properties Oxidising properties : No data available Vapour pressure : No data available No data available Relative density Relative vapour density at 20 °C No data available Density : >= 1.085 g/ml

Water: Solubility in water of component(s) of the mixture :

Soluble in water.

• disodium metasilicate: > 18 g/100ml • dipropylene glycol monomethyl ether: Complete •

potassium hydroxide: 112 g/100ml • 2-aminoethanol: Complete

Log Pow : No data available
Log Kow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

9.2. Other information

VOC content : <= 54 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Solubility

Thermal decomposition generates: Corrosive vapours.

10.2. Chemical stability

Not established. Combustible liquid.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates: Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

disodium metasilicate (6834-92-0)		
LD50 dermal rat	> 5000 mg/kg bodyweight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)	
potassium hydroxide (1310-58-3)		
LD50 oral rat	333 mg/kg (Rat; Equivalent or similar to OECD 425; Experimental value)	
ATE US (oral)	333.000 mg/kg bodyweight	
2-aminoethanol (141-43-5)		
LD50 oral rat	1720 mg/kg (Rat)	
LD50 dermal rabbit	1018 mg/kg (Rabbit)	

01/17/2017 EN (English) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-aminoethanol (141-43-5)	
ATE US (oral)	1720.000 mg/kg bodyweight
ATE US (dermal)	1018.000 mg/kg bodyweight
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
	pH: >= 13
Serious eye damage/irritation	: Not classified
	pH: >= 13
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified

exposure)

: Not classified Aspiration hazard

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

Toxicity

disodium metasilicate (6834-92-0)		
LC50 fish 1	210 mg/l (LC50; Equivalent or similar to OECD 203; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)	
Threshold limit algae 1	207 mg/l (EC50; DIN 38412-9; 72 h; Scenedesmus subspicatus; Fresh water)	
potassium hydroxide (1310-58-3)		
LC50 fish 2	80 mg/l (LC50; 96 h; Gambusia affinis; Static system; Fresh water)	
2-aminoethanol (141-43-5)		
LC50 fish 1	150 mg/l (LC50; 96 h; Salmo gairdneri)	
EC50 Daphnia 1	140 mg/l (EC50; 24 h)	
Threshold limit algae 2	35 mg/l (EC50; 72 h)	

Persistence and degradability 12.2.

Tank Cleaner		
Persistence and degradability	Not established.	
disodium metasilicate (6834-92-0)		
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
potassium hydroxide (1310-58-3)		
Persistence and degradability	Biodegradability: not applicable.	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
2-aminoethanol (141-43-5)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.	
Biochemical oxygen demand (BOD)	0.80 g O₂/g substance	
Chemical oxygen demand (COD)	1.34 g O₂/g substance	

01/17/2017 EN (English) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-aminoethanol (141-43-5)	
ThOD	2.49 g O₂/g substance
BOD (% of ThOD)	0.32

12.3. Bioaccumulative potential

Tank Cleaner		
Bioaccumulative potential	Not established.	
disodium metasilicate (6834-92-0)		
Bioaccumulative potential	Bioaccumulation: not applicable.	
potassium hydroxide (1310-58-3)		
Bioaccumulative potential	Bioaccumulation: not applicable.	
2-aminoethanol (141-43-5)		
Log Pow	-1.91	
Bioaccumulative potential	Bioaccumulation: not applicable.	

12.4. Mobility in soil

2-aminoethanol (141-43-5)	
Surface tension	0.050 N/m

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s. (Contains Sodium Hydroxide), 8, III

UN-No.(DOT) : UN1760

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.

Contains Sodium Hydroxide

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

01/17/2017 EN (English) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

: 154

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information : Consumer Commodity ORM-D for 128oz or less.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

disodium metasilicate (6834-92-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

potassium hydroxide (1310-58-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporing requirements of the United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's

List of Lists)

1000 lb

2-aminoethanol (141-43-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

01/17/2017 EN (English) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

National regulations

No additional information available

15.3. US State regulations

potassium hydroxide (1310-58-3)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

2-aminoethanol (141-43-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information : None.

Full text of H-statements:

W of 11 of the first	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 3	Hazardous to the aquatic environment — Acute Hazard, Category 3
Flam. Liq. 4	Flammable liquids, Category 4
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H402	Harmful to aquatic life

NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was

given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

NFPA specific hazard : None

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal Protection : C

C - Safety glasses, Gloves, Synthetic apron

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

01/17/2017 EN (English) 8/8