according to the OSHA Hazard Communication Standard



# **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

### **SECTION 1. IDENTIFICATION**

Product name : TEMPO ULTRA WP10

Product code : Article/SKU: 02903524 UVP: 03545575 Specification:

102000016285 EPA Registration No: 101563-59

Manufacturer or supplier's details

Company name of supplier : Environmental Science U.S. LLC.

Address : 5000 Centregreen Way, Suite 400

Cary NC 27513

Telephone : 1-800-331-2867

Emergency telephone : +1 703-741-5970

E-mail address : uscontact@envu.com

Recommended use of the chemical and restrictions on use

Recommended use : Insecticide

Restrictions on use : See product label for restrictions.

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Eye irritation : Category 2B

Effects on or via lactation

**GHS** label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : May form combustible dust concentrations in air.

H302 + H332 Harmful if swallowed or if inhaled.

H320 Causes eye irritation.

according to the OSHA Hazard Communication Standard



### **TEMPO ULTRA WP10**

Version SDS Number: Revision Date: Date of last issue: -

09/08/2023 11269343-00001 Date of first issue: 09/08/2023 1.0

H362 May cause harm to breast-fed children.

**Precautionary Statements** Prevention:

P201 Obtain special instructions before use.

P260 Do not breathe dust.

P263 Avoid contact during pregnancy and while nursing.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel

unwell. Rinse mouth.

P304 + P340 + P312 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical attention.

P337 + P313 If eye irritation persists: Get medical attention.

P501 Dispose of contents and container to an approved waste

disposal plant.

#### Other hazards

Cutaneous sensations may occur, such as burning or stinging on the face and mucosae. However, these sensations cause no lesions and are of a transitory nature (max. 24 hours).

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Chemical nature Wettable powder (WP)

### Components

Chemical name	CAS-No.	Concentration (% w/w)
beta-Cyfluthrin (ISO)	1820573-27-0	>= 10 - < 20
Quartz	14808-60-7	>= 5 - < 10
Naphthalenesulfonic acid, bis(1-	68909-82-0	>= 1 - < 5
methylethyl)-, Methyl derivatives,		
sodium salts		

Actual concentration is withheld as a trade secret

# **SECTION 4. FIRST AID MEASURES**

General advice In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

according to the OSHA Hazard Communication Standard



### **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting unless directed to do

so by medical personnel. Get medical attention.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

delayed

No symptoms known or expected.

Harmful if swallowed or if inhaled.

Causes eye irritation.

May cause harm to breast-fed children. This product contains a pyrethroid.

Pyrethroid poisoning should not be confused with carbamate

or organophosphate poisoning.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Appropriate supportive and symptomatic treatment as indica-

ted by the patient's condition is recommended.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Avoid generating dust; fine dust dispersed in air in sufficient

concentrations, and in the presence of an ignition source is a

potential dust explosion hazard.

Do not use a solid water stream as it may scatter and spread

fire.

Exposure to combustion products may be a hazard to health.

according to the OSHA Hazard Communication Standard



### TEMPO ULTRA WP10

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

Hazardous combustion prod-

ucts

Carbon oxides
Chlorine compounds

Fluorine compounds Nitrogen oxides (NOx)

Metal oxides Sulfur oxides Silicon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Surround spill with absorbents and place a damp covering over the area to minimize entry of the material into the air. Add excess liquid to allow the material to enter into solution.

Soak up with inert absorbent material.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.

Sed into the atmosphere in sufficient concentration.

Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : Static electricity may accumulate and ignite suspended dust

according to the OSHA Hazard Communication Standard



# TEMPO ULTRA WP10

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

causing an explosion.

Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Avoid contact during pregnancy and while nursing.

Do not get on skin or clothing.

Do not breathe dust. Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep container tightly closed.

Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition. Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

inert or nuisance dust 50 Million particles per cubic foot

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

15 mg/m<sup>3</sup>

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

5 mg/m<sup>3</sup>

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

15 Million particles per cubic foot

Value type (Form of exposure): TWA (respirable fraction)

according to the OSHA Hazard Communication Standard



### **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

Basis: OSHA Z-3

Dust, nuisance dust and par-

ticulates

10 mg/m<sup>3</sup>

Value type (Form of exposure): PEL (Total dust)

Basis: CAL PEL

5 mg/m<sup>3</sup>

Value type (Form of exposure): PEL (respirable dust fraction)

Basis: CAL PEL

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz	14808-60-7	TWA (Res-	0.05 mg/m <sup>3</sup>	OSHA Z-1
Quartz	14000-00-7	pirable dust)	0.05 1119/111	0311A Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respir-	250 mppcf	OSHA Z-3
		able)	/ %SiO2+5	

# **Engineering measures**

Minimize workplace exposure concentrations.

Apply measures to prevent dust explosions.

Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). If sufficient ventilation is unavailable, use with local exhaust

ventilation.

### Personal protective equipment

Respiratory protection

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special

according to the OSHA Hazard Communication Standard



# **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro-

duct. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : tan

Odor : characteristic

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower

flammability limit

Not applicable

Vapor pressure : Not applicable

according to the OSHA Hazard Communication Standard



# **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

Relative vapor density : Not applicable

Density : No data available

Bulk density : 304 - 416 kg/m<sup>3</sup>

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Minimum ignition energy : > 10 mJ

Particle size :  $>= 6 \mu m$ 

 $<=35 \mu m$ 

### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Dust can form an explosive mixture in air. Can react with strong oxidizing agents.

Conditions to avoid : Avoid dust formation.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

according to the OSHA Hazard Communication Standard



# **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

### Acute toxicity

Harmful if swallowed or if inhaled.

**Product:** 

Acute oral toxicity : LD50 (Rat): 1,733 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 1.18 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

**Components:** 

beta-Cyfluthrin (ISO):

Acute oral toxicity : LD50 (Rat): 11 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.081 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 402

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Acute oral toxicity : LD50 (Rat, female): > 300 - 2,000 mg/kg

Method: OECD Test Guideline 423

Skin corrosion/irritation

Not classified based on available information.

**Components:** 

beta-Cyfluthrin (ISO):

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Species : Rabbit

according to the OSHA Hazard Communication Standard



# **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

Method : OECD Test Guideline 404

Result : Skin irritation

### Serious eye damage/eye irritation

Causes eye irritation.

**Product:** 

Species : Rabbit

Result : Irritation to eyes, reversing within 7 days

**Components:** 

beta-Cyfluthrin (ISO):

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Species : Bovine cornea

Method : OECD Test Guideline 437

Result : Irreversible effects on the eye

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

**Components:** 

beta-Cyfluthrin (ISO):

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Test Type : Direct Peptide Reactivity Assay (DPRA)

Method : OECD Test Guideline 442C

Result : equivocal

Test Type : KeratinoSens assay

Method : OECD Test Guideline 442D

Result : negative

Test Type : Dendritic cell activation test Method : OECD Test Guideline 442E

according to the OSHA Hazard Communication Standard



# **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

Result : negative

Assessment : Does not cause skin sensitization.

### Germ cell mutagenicity

Not classified based on available information.

#### **Components:**

beta-Cyfluthrin (ISO):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

### Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

### Carcinogenicity

Not classified based on available information.

### **Components:**

### beta-Cyfluthrin (ISO):

Species : Mouse
Application Route : Ingestion
Exposure time : 18 Months
Result : negative

Remarks : Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

May cause harm to breast-fed children.

### **Components:**

### beta-Cyfluthrin (ISO):

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

according to the OSHA Hazard Communication Standard



# TEMPO ULTRA WP10

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

Application Route: Ingestion

Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 426

Result: negative

Reproductive toxicity - As-

sessment

Studies indicating a hazard to babies during the lactation peri-

od

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

STOT-single exposure

Not classified based on available information.

**Product:** 

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Components:

beta-Cyfluthrin (ISO):

Routes of exposure : Ingestion

Target Organs : Nervous system

Assessment : Shown to produce significant health effects in animals at con-

centrations of 300 mg/kg bw or less.

Routes of exposure : Skin contact
Target Organs : Nervous system

Assessment : Shown to produce significant health effects in animals at con-

centrations of 1000 mg/kg bw or less.

STOT-repeated exposure

Not classified based on available information.

according to the OSHA Hazard Communication Standard



# **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

### Repeated dose toxicity

#### **Components:**

### Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Species : Rat

NOAEL : 200 mg/kg

LOAEL : 700 mg/kg

Application Route : Ingestion

Exposure time : 54 Days
Method : OECD Test Guideline 422

Aspiration toxicity

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

#### **Components:**

beta-Cyfluthrin (ISO):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.068 µg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Hyalella azteca (Amphipod)): > 0.0001 - 0.001 μg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): > 0.001 - 0.01

μg/l

Exposure time: 58 d

Remarks: Based on data from similar materials

#### Quartz:

### **Ecotoxicology Assessment**

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

### Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Raphidocelis subcapitata (freshwater green alga)): >

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

according to the OSHA Hazard Communication Standard



# **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

Method: OECD Test Guideline 201

EL10 (Raphidocelis subcapitata (freshwater green alga)): 14.8

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

### Persistence and degradability

# **Components:**

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301D

### Bioaccumulative potential

### **Components:**

beta-Cyfluthrin (ISO):

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): 1,508 Method: OECD Test Guideline 305

Partition coefficient: n-

octanol/water

log Pow: 5.8 - 5.9

### Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Partition coefficient: n-

octanol/water

: log Pow: 0

### Mobility in soil

No data available

#### Other adverse effects

No data available

# **SECTION 13. DISPOSAL CONSIDERATIONS**

# Disposal methods

Waste from residues : It is best to use all of the product in accordance with label

directions. If it is necessary to dispose of unused product, please follow container label instructions and applicable local

guidelines.

Do not dispose of waste into sewer.

Contaminated packaging : Follow advice on product label and/or leaflet.

Empty containers retain residue and can be dangerous.

according to the OSHA Hazard Communication Standard



# **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

Do not re-use empty containers.

#### **SECTION 14. TRANSPORT INFORMATION**

### **International Regulations**

**UNRTDG** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(beta-Cyfluthrin (ISO))

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

**IATA-DGR** 

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(beta-Cyfluthrin (ISO))

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo :

aircraft)

Packing instruction (passen: 956

ger aircraft)

Environmentally hazardous : yes

**IMDG-Code** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

956

(beta-Cyfluthrin (ISO))

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**Domestic regulation** 

**49 CFR** 

UN/ID/NA number : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(beta-Cyfluthrin (ISO))

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171

Marine pollutant : yes(beta-Cyfluthrin (ISO))

Remarks : Above applies only to containers over 119 gallons or 450 li-

according to the OSHA Hazard Communication Standard



### **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

ters.

Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

Acute toxicity (any route of exposure)

Reproductive toxicity

Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### **US State Regulations**

### Pennsylvania Right To Know

Fuller's Earth
8031-18-3
tributyl O-acetylcitrate
77-90-7
beta-Cyfluthrin (ISO)
1820573-27-0
Quartz
14808-60-7
Lignosulfonic acid, sodium salt
Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl deriva68909-82-0

tives, sodium salts

### California Permissible Exposure Limits for Chemical Contaminants

Quartz 14808-60-7

Product Type : Insecticides, acaricides and products to control other arthro-

pods

Active substance : 10 %

beta-Cyfluthrin (ISO)

according to the OSHA Hazard Communication Standard



### TEMPO ULTRA WP10


Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

CAL PEL : California permissible exposure limits for chemical contami-

nants (Title 8, Article 107)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

CAL PEL / PEL : Permissible exposure limit
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Oth-

according to the OSHA Hazard Communication Standard



# **TEMPO ULTRA WP10**

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/08/2023 11269343-00001 Date of first issue: 09/08/2023

erwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to

compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 09/08/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8