

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** WIL-GRO WIL-COTE Hybrid Special 21-3-21  
**Other means of identification** None.  
**Recommended use** Ag Product - Plant Nutrition  
**Recommended restrictions** Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

### Manufacturer/Importer/Supplier/Distributor information

#### Manufacturer

**Company name** Wilbur-Ellis Company LLC  
**Address** Wilbur-Ellis Company LLC  
8131 W. Grandbridge Blvd, Suite 200  
Kennewick, WA 99336  
United States  
**Telephone** Branded Products Information (800) 500-1698  
**E-mail** SDS@WilburEllis.com  
**Emergency phone number** Chemtrec - Domestic (800) 424-9300  
Chemtrec - International +1 703-741-5970

## 2. Hazard(s) identification

**Physical hazards** Not classified.  
**Health hazards** Carcinogenicity Category 1A  
**OSHA defined hazards** Not classified.

#### Label elements



**Signal word** Danger  
**Hazard statement** May cause cancer.  
**Precautionary statement**  
**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection, and face protection.  
**Response** IF exposed or concerned: Get medical attention.  
**Storage** Store locked up.  
**Disposal** Dispose of contents and container in accordance with government regulations.  
**Hazard(s) not otherwise classified (HNOC)** None known.  
**Supplemental information** None.

## 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Urea		57-13-6	40 - < 50
Ammonium Phosphate		7722-76-1	5 - < 10
Ammonium Sulfate		7783-20-2	3 - < 5
Manganese Sulfate		10034-96-5	1 - < 3

Chemical name	Common name and synonyms	CAS number	%
Sulfur		7704-34-9	1 - < 3
Respirable Crystalline Silica		14808-60-7	< 0.2
Other components below reportable levels			40 - < 50

Percentage ranges of composition to protect confidentiality or due to batch variation.

#### 4. First-aid measures

<b>Inhalation</b>	If dust from the material is inhaled, remove the affected person immediately to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Rinse skin with water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.
<b>Most important symptoms/effects, acute and delayed</b>	Irritation of eyes. Upper respiratory tract irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Use water spray to cool unopened containers.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust from the spilled material. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Stop the flow of material, if this is without risk. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Collect dust using a vacuum cleaner equipped with HEPA filter. Minimize dust generation and accumulation. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.

#### 7. Handling and storage

<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide appropriate exhaust ventilation at places where dust is formed. Minimize dust generation and accumulation. Do not breathe dust. Avoid contact with eyes. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities</b>	Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Manganese Sulfate (CAS 10034-96-5)	Ceiling	5 mg/m <sup>3</sup>

#### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Respirable Crystalline Silica (CAS 14808-60-7)	TWA	0.3 mg/m <sup>3</sup>	Total dust.
		0.1 mg/m <sup>3</sup>	Respirable.
		2.4 mppcf	Respirable.

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Manganese Sulfate (CAS 10034-96-5)	TWA	0.1 mg/m <sup>3</sup>	Inhalable fraction.
		0.02 mg/m <sup>3</sup>	Respirable fraction.
Respirable Crystalline Silica (CAS 14808-60-7)	TWA	0.025 mg/m <sup>3</sup>	Respirable fraction.

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Manganese Sulfate (CAS 10034-96-5)	STEL	3 mg/m <sup>3</sup>	Fume.
	TWA	1 mg/m <sup>3</sup>	Fume.
Respirable Crystalline Silica (CAS 14808-60-7)	TWA	0.05 mg/m <sup>3</sup>	Respirable dust.

#### US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
Urea (CAS 57-13-6)	TWA	10 mg/m <sup>3</sup>	Total particulate.

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.

#### Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

**Other** Wear suitable protective clothing. Use of an impervious apron is recommended.

**Respiratory protection** Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

**Physical state** Solid.

<b>Form</b>	Powder.
<b>Color</b>	Not available.
<b>Odor</b>	Not available.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>VOC (Weight %)</b>	41.27 % Switzerland estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Inhalation of dusts may cause respiratory irritation. Prolonged inhalation may be harmful.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Dust in the eyes will cause irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** Irritation of eyes. Upper respiratory tract irritation.

### Information on toxicological effects

#### Acute toxicity

Components	Species	Test Results
Ammonium Phosphate (CAS 7722-76-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
	Rat	> 5000 mg/kg, 24 Hours
<i>Oral</i>		
LD50	Rat	3260 mg/kg
Ammonium Sulfate (CAS 7783-20-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Mouse	> 2000 mg/kg
	Rat	> 2000 mg/kg
<i>Oral</i>		
LD50	Rat	4250 mg/kg
Manganese Sulfate (CAS 10034-96-5)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	> 4.45 mg/l, 4 Hours
<i>Oral</i>		
LD50	Mouse	2330 mg/kg
	Rat	2150 mg/kg
Sulfur (CAS 7704-34-9)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg, 24 Hours
<i>Oral</i>		
LD50	Rat	> 2200 mg/kg
Urea (CAS 57-13-6)		
<b>Acute</b>		
<i>Oral</i>		
LD50	Mouse	13000 mg/kg
	Rat	15000 mg/kg
<i>Other</i>		
LD50	Mouse	9200 mg/kg
	Rat	8200 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.
<b>Serious eye damage/eye irritation</b>	Dust in the eyes will cause irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not available.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

## Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Respirable Crystalline Silica (CAS 14808-60-7) 1 Carcinogenic to humans.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### US. National Toxicology Program (NTP) Report on Carcinogens

Respirable Crystalline Silica (CAS 14808-60-7) Known To Be Human Carcinogen.

<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not available.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

<b>Ecotoxicity</b>	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
<b>Persistence and degradability</b>	No data is available on the degradability of this product.
<b>Bioaccumulative potential</b>	No data available.
<b>Partition coefficient n-octanol / water (log Kow)</b>	
Urea	-2.11
<b>Mobility in soil</b>	No data available.
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents and container in accordance with government regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

### DOT

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

**IMDG**

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Manganese Sulfate (CAS 10034-96-5) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - No  
Delayed Hazard - Yes  
Fire Hazard - No  
Pressure Hazard - No  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
AMMONIA (INCLUDES ANHYDROUS AMMONIA AND AQUEOUS AMMONIA FROM WATER DISSOCIABLE AMMONIUM SALTS AND OTHER SOURCES; 10% OF TOTAL AQUEOUS AMMONIA IS REPORTABLE UNDER THIS LISTING)	7722-76-1	5 - < 10
AMMONIA (INCLUDES ANHYDROUS AMMONIA AND AQUEOUS AMMONIA FROM WATER DISSOCIABLE AMMONIUM SALTS AND OTHER SOURCES; 10% OF TOTAL AQUEOUS AMMONIA IS REPORTABLE UNDER THIS LISTING)	7783-20-2	3 - < 5
MANGANESE COMPOUNDS	10034-96-5	1 - < 3

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Manganese Sulfate (CAS 10034-96-5)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. Massachusetts RTK - Substance List**

Ammonium Sulfate (CAS 7783-20-2)  
Respirable Crystalline Silica (CAS 14808-60-7)  
Sulfur (CAS 7704-34-9)

**US. New Jersey Worker and Community Right-to-Know Act**

Manganese Sulfate (CAS 10034-96-5)

