

CrossGuard®

DEPOSITION AID • DRIFT REDUCTION AGENT

PRINCIPAL FUNCTIONING AGENTS:

Modified vegetable oil, Amine salts of organic acids, and Organic acids 100%

CA Reg. No. 94100-50008

PRODUCT INFORMATION

CrossGuard® is a spray adjuvant designed to improve pesticide deposition on the intended target, achieving an increased level of performance of most pesticides. Use of this product in a typical spray application will help reduce the number of drift-able fines that can occur when pesticides are applied by ground or air. When used in conjunction with proper spray equipment selections, this unique formulation will help manage the spray pattern, allowing for better coverage of agricultural, forestry, industrial, and non-cropland sites. Not for aquatic use.

NOTE: CrossGuard does not replace the need for additional adjuvants in the spray tank.

DIRECTIONS FOR USE

Read and follow the pesticide label for proper timing, rates, specific directions and any special use precautions. Use this product in accordance with the instructions found on the pesticide label regarding adjuvants. In the absence of specific instructions, follow the recommendations below which are considered adequate for most uses.

RECOMMENDATIONS: Optimum use rates can be affected by conditions of application such as water hardness, application method, equipment, spray droplet size, spray nozzle selection, or condition or size of foliage. Therefore, carefully observe spray deposition and adjust adjuvant rate accordingly to ensure thorough coverage without excessive runoff.

For pesticides that permit use of an adjuvant at a higher rate, follow instructions on that pesticide label. However, do not add this product at a rate which exceeds 5% of the finished spray volume. Use caution at the higher use rates. When applying to a sensitive crop, first treat a small area to determine if there are any adverse effects to the crop.

Use	Rate per Acre
Fungicides Herbicides Insecticides	4 fl oz

MIXING: Shake well before use. Fill spray tank 2/3 full of water and begin agitation. Add tank mix partners, starting with water conditioner, as directed by label or in the following sequence and continue filling tank: (1) Dry flowables or water dispersing granules, (2) Wettable powders, (3) Flowables, (4) Solutions, and (5) Emulsifiable concentrates. **Add the desired amount of**

CrossGuard last, unless otherwise directed. Continuous agitation of finished spray is recommended throughout the spray operation. If spray solution has been allowed to stand, thoroughly remix before application. For best results, apply within 24 hours after mixing.

COMPATIBILITY: CrossGuard is compatible with most pesticides. However, if the desired combination has not been previously used, a compatibility test is recommended.

KEEP OUT OF REACH OF CHILDREN



WARNING: May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Wear protective gloves. Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace.

FIRST AID: Have the product container or label with you when calling a poison control center or doctor or going for treatment. If on skin: Wash with plenty of water. If skin irritation or rash occurs, Get medical attention. Wash contaminated clothing before reuse.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage, disposal or cleaning of equipment. Store in original container only and keep tightly sealed when not in use. Store away from incompatible materials. Do not allow this product to freeze.

Nonrefillable container. Do not reuse or refill this container. Triple rinse (or equivalent) during mixing and loading and add rinsate to spray tank. Recycling decontaminated containers is the best option of container disposal. The Agricultural Container Recycling Council (ACRC) operates the national recycling program. To contact your state or local ACRC recycler, visit the ACRC web page at www.agrecycling.org. Decontaminated containers may also be disposed of in a sanitary landfill in a manner allowed by local, state and federal laws and regulations.

LIMITATION OF WARRANTY AND LIABILITY

To access Red Zone Technologies' warranty statement, please go to rztproducts.com/warranty.

All trademarks, service marks, trade names, trade dress, product names and logos appearing on this label are the property of their respective owners.

NET CONTENTS: ___ gal / ___ L

Typical density: 7.34 lb/gal @ 68° F



RED ZONE TECHNOLOGIES
PO BOX 5471, FRESNO, CA 93755