

Granular Humic

0-0-10

GUARANTEED ANALYSIS

Soluble Potash (K₂O).....10.00%

Derived from Potassium Hydroxide.

ALSO CONTAINS NON-PLANT FOOD INGREDIENT:

95.00% Humic Acids derived from Sub-Bituminous Coals.

F3445

GENERAL INFORMATION

Granular Humic dry granules are extracted, refined, water-soluble humic acids that may aid in the uptake of micronutrients. This product can be blended with most dry fertilizers, including urea blends, and may be applied to most crops.

DIRECTIONS FOR USE

Consult your local agronomist for rates specific to your crop and conditions.

Do not apply near water, storm drains, or drainage ditches, or to any impervious surface. Do not apply if heavy rain is expected. Apply this product only to the intended application site.

SOIL: Broadcast, band, or prepare seed or transplant bed with 1-20 pounds per acre with dry fertilizer program. If applying with seed or in-season, incorporate with water or tillage. Multiple applications can be beneficial.

SEEDING: Band or broadcast 1-5 pounds with seed on cereal crops at planting.

COMPATIBILITY: Granular Humic is formulated to be mixed with most dry blends. Do not mix with fertilizers containing calcium or solution with low pH.

Proper mixing procedure:

1. Add all dry NPK and micros to blender
2. Add desired rate of Granular Humic
3. Blend until homogenous

In areas of high humidity or when adding AMS/urea blends, use of a drying agent is recommended.

PRECAUTIONARY STATEMENTS

KEEP OUT OF REACH OF CHILDREN

Based on currently available data, this product is not classified as a GHS hazardous substance. However, observe good industrial hygiene practices. Wash hands after handling. Refer to the Safety Data Sheet if first aid instructions are needed.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage, disposal or cleaning of equipment. Store in original container only and keep tightly sealed when not in use. Store away from incompatible materials. Dispose of contents/container in accordance with federal, state and local regulations.

LIMITATION OF WARRANTY AND LIABILITY

To access Red Zone Technologies' warranty statement, please go to rztproducts.com/warranty.

All trademarks, service marks, trade names, trade dress, product names and logos appearing on this label are the property of their respective owners.

RZT233108



RED ZONE TECHNOLOGIES
PO BOX 5471, FRESNO, CA 93755

NET WEIGHT: 55 POUNDS (25 kg)