# ShackLock

## **Water Conditioner and Drift Control**

## CHELATES METALLIC IONS, WETTING AGENT/NONIONIC SURFACTANT, DRIFT CONTROL

#### GENERAL INFORMATION

ShackLock is industry leading triple mode adjuvant technology. With ShackLock, you go to the field with our expert chelating water conditioner, proven to decrease volatility, paired with our next generation polymer drift control, and premium wetting/surfactant technology. Using ShackLock, you reduce product needed for tank mixing, while lowering cost per acre and getting tremendous results with all of todays new chemistries. This easy to use adjuvant is a great water conditioner, drift control agent, and non-ionic surfactant all-in-one, meeting the demand for Non-AMS water conditioning.

#### HANDLING AND STORAGE

Do not breathe mist or vapors. Wash hands, forearms, face, and clothing thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, and protective gloves. Absorb spillage to prevent material damage. Store in a locked corrosive resistant container with a resistant inner liner. Dispose of contents or container at a licensed hazardous waste disposal contractor or collection site, except for empty clean containers, which can be disposed of as non-hazardous waste.

#### **DIRECTIONS FOR USE**

Always add ShackLock to water before adding glyphosate.

#### FIRST AID

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF EXPOSED OR CONCERNED: Get medical advice/attention if you feel unwell. Immediately call a POISON CONTROL CENTER at 800-222-1222.

IF SKIN IRRITATION OCCURS: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

# CAUTION: KEEP OUT OF REACH OF CHILDREN

May cause skin and eye irritation. Avoid eye and skin contact. Do not take internally.

### **NET CONTENTS:**

2.5 U.S. GALLONS (9.46 L)

#### RATE OF SHACKLOCK

- •The application rate is 2-8 quarts per 100 gallons of water
- •Follow chemical label recommendations for water conditioners

Important: This product has demonstrated excellent plant safety; however, not all species and varieties have been tested. Before treating a large area, treat a small area and observe prior to full scale application.

#### **INGREDIENTS:**


Principal Functioning Agents: Inert Composition	
Inert Composition	5%
Water Conditioning Agents	45%
Polyvinyl Polymer Encapsulation	Blend
(Polyacrylamide non-reactive)	50%
Total	100%

All ingredients are exempt from tolerance requirements under 40 CFR 180.1001(d)



**888-679-5103** www.egebio.com PO Box 538 Minneola, KS 67865







May be corrosive to metals. Causes skin irritation. Causes serious eye damage.



Harmful if inhaled. Suspected of causing cancer. May cause damage to organs (Respiratory tract) through prolonged or repeated exposure (Inhalation).